



Continuous Mini Lab. Tenter CMT

Model:

- CMT-P (pin type)

Application:

- Drying
- Heat-setting
- Thermosol fixation
- Printing fixation



Features:

- 3×hot flue chamber.
- 2×UPC controller temp. setting and control.
- Auto ventdoor control.
- Each chamber contained of individual upper / lower blower motor and control.
- Pin-frame chain.
- Drying or heat setting temp to.220°C
- Dwell time 0-6m/min
- Pin-frame sample width adjustment 160-330mm
- Circulate hot air
- Fabric take on wheel
- Fabric take off device

Option:

- Link up with padder & pad trough.

Specification:

	CMT-P 400
Sample width	160-330 mm
Chamber capacity	≈1.8 m
Power (KW)	18KW/3 phase
Voltage	3 phase 380V
Current	47.5A
Machine dimension (W×D×H mm)	2620×890×1380 mm
Machine weight	750 kg

KMS COLORTECH SERVICE CO., LTD.

Unit 2005 Metro Centre II , 21 Lam Hing Street, Kowloon Bay, Hong Kong.

TEL: (852) 2753 6176 FAX: (852) 2753 6049

E-mail: sales@kmscolor.com / kmsgz@vip.163.com WEBSITE: www.kmscolor.com