

Lab Dyeing Machine LM-DT

Features:

- (1) Rotating dyeing motion
- (2) **Application** most on cotton dyeing and such as 60°C constant temp. bath dyeing. Suitable for different kind of fabric, yarn, and materials, as on request of 130°C water cooling pipe (option).
- (3) **UPC-Touch screen controller** with graphic display and 100 program storage for curve dyeing too.
- (4) Standard: 24 position carrier × 350ml dyetube
- (5) Provide of dyeing dyetube:
 - Flat type lid.

Options:

- 24 position carrier × 500ml dyetube
- 16 position carrier × 1000ml dyetube
- 4 position carrier × 3000ml dyetube
- carrier and wash pots for washing colorfastness testing or soaping.

Accessories: -

yarn sample holder, Fabric sample foil holder.

Specification:

Machine dim. (W×D×H)	1065×708×1040mm
Machine net weight	Approx. 140 kg
Wattage	3-phase 4 kw
Power	3-phase 380V/50Hz

HONGKONG

KMS COLORTECH SERVICE CO. LTD

Rm104K, Unit4~5, On1/Floor,Yuen Fat Industrial Building,No25, Wang Chiu Road Kowloon Bay Kowloon, Hong Kong TEL: (852) 2753 6176 FAX: (852) 2753 6049

CHINA

